ELSEVIER
Solar Energy Materials and Solar Cells 40 (1996) 381–383
Solar Energy Materials and Solar Cells

Author index to volume 40

Adurodija, F.O., M.J. Carter and R. Hill, Synthesis and characterization of $\mathrm{CuInSe_2}$ thin films from Cu, In and Se stacked layers using a closed graphite box 40 (1996) 359
Al-Dhafiri, A.M., Electrical properties of UV photochemically treated CdTe 40 (1996) 221
Alkemade, P.F.A., see Leguijt, C. 40 (1996) 297
Araújo, G.L., see Ragay, F.W. 40 (1996) 5
Archer, M.D., J.R. Bolton and S.T.C. Siklos, A review of analytic solutions for a model *p-n* junction cell under low-injection conditions 40 (1996) 133
Attubato, L., see Malati, M.A. 40 (1996) 1

Beaney, K., see Malati, M.A. 40 (1996) 1
Blakers, A.W., see Stocks, M.J. 40 (1996) 33
Bolton, J.R., see Archer, M.D. 40 (1996) 133
Braunger, D., D. Hariskos, T. Walter and H.W. Schock, An 11.4% efficient polycrystalline thin film solar cell based on $\mathrm{CuInS_2}$ with a Cd-free buffer layer 40 (1996) 97
Burger, D.R., see Lin, J.J. 40 (1996) 177

Carr, A.J., see Stocks, M.J. 40 (1996) 33
Carter, M.J., see Adurodija, F.O. 40 (1996) 359
Caudano, R., see Diatezua, D.M. 40 (1996) 253
Chartier, P., see Nguyen Cong, H. 40 (1996) 261
Chen, E., see Zheng, G.F. 40 (1996) 89
Chen, Y.P., see Ma, H.L. 40 (1996) 371
Choi, J.C., S.D. Kim and G.Y. Han, Heat transfer characteristics in low-temperature latent heat storage systems using salt-hydrates at heat recovery stage 40 (1996) 71
Crnjak Orel, Z. and B. Orel, Structural and electrochemical properties of $\mathrm{CeO_2}$ and mixed $\mathrm{CeO_2/SnO_2}$ coatings 40 (1996) 205

Dereux, A., see Diatezua, D.M. 40 (1996) 253
Diatezua, D.M., P.A. Thiry, A. Dereux and R. Caudano, Silicon oxynitride multilayers as spectrally selective material for passive radiative cooling applications 40 (1996) 253

Ebong, A.U., M. Taouk, C.B. Honsberg and S.R. Wenham, The use of oxynitrides for the fabrication of buried contact silicon solar cells 40 (1996) 183
Eikelboom, J.A., see Leguijt, C. 40 (1996) 297

Ghazali, A., see Zainal, Z. 40 (1996) 347
Green, M.A., see Zheng, G.F. 40 (1996) 231
Gross, M., see Zheng, G.F. 40 (1996) 89
Gross, M., see Zheng, G.F. 40 (1996) 231

Han, G.Y., see Choi, J.C. 40 (1996) 71
Hariskos, D., see Braunger, D. 40 (1996) 97
Hill, R., see Adurodija, F.O. 40 (1996) 359
Hinsch, A., see Varol, H.S. 40 (1996) 273
Honsberg, C.B., see Ebong, A.U. 40 (1996) 183
Hussein, M.Z., see Zainal, Z. 40 (1996) 347
Hutchins, M.G., see Orel, Z.C. 40 (1996) 197

Kim, S.D., see Choi, J.C. 40 (1996) 71

Lampert, C.M., see Özer, N. 40 (1996) 285
Leguijt, C., P. Lölgen, J.A. Eikelboom, A.W. Weeber, F.M. Schuurmans, W.C. Sinke, P.F.A. Alkemade, P.M. Sarro, C.H.M. Marée and L.A. Verhoef, Low temperature surface passivation for silicon solar cells 40 (1996) 297
Leskovšek, N., see Orel, Z.C. 40 (1996) 197
Li, S.Y., see Ma, H.L. 40 (1996) 371
Lin, J.J. and D.R. Burger, TPV cell *IV* curve testing with varying black body emission temperatures, intensities, and cell temperatures 40 (1996) 177
Lölgen, P., see Leguijt, C. 40 (1996) 297

Ma, H.L., D.H. Zhang, S.Z. Win, S.Y. Li and Y.P. Chen, Electrical and optical properties of F-doped textured SnO_2 films deposited by APCVD 40 (1996) 371
Malati, M.A., L. Attubato and K. Beaney, Efficient photocatalysts for the reduction of aqueous carbonate and Cr(VI) 40 (1996) 1
Marée, C.H.M., see Leguijt, C. 40 (1996) 297
Martí, A., see Ragay, F.W. 40 (1996) 5
Mills, D.R., see Zhang, Q.-C. 40 (1996) 43

Ndukwe, I.C., Solution growth, characterization and applications of zinc sulphide thin films 40 (1996) 123
Nguyen Cong, H., C. Sene and P. Chartier, Poly(3-methylthiophene) structural change effect on characteristics of CdS(Al):PMeT photovoltaic junction 40 (1996) 261
Nilsson, T., Initial experiments on dew collection in Sweden and Tanzania 40 (1996) 23

Orel, B., see Crnjak Orel, Z. 40 (1996) 205
Orel, B., see Orel, Z.C. 40 (1996) 197
Orel, Z.C., N. Leskovšek, B. Orel and M.G. Hutchins, Spectrally selective silicon paint coatings: Influence of pigment volume concentration ratio on their optical properties 40 (1996) 197
Özer, N., M.D. Rubin and C.M. Lampert, Optical and electrochemical characteristics of niobium oxide films prepared by sol-gel process and magnetron sputtering. A comparison 40 (1996) 285

Ragay, F.W., A. Martí, G.L. Araújo and J.H. Wolter, Experimental analysis of the efficiency of heterostructure GaAs–AlGaAs solar cells 40 (1996) 5
Rodriguez, J., see Yang, Y. 40 (1996) 103
Rubin, M.D., see Özer, N. 40 (1996) 285

Sabisky, E.S., A minimum achievable PV electrical generating cost 40 (1996) 55
Sarro, P.M., see Leguijt, C. 40 (1996) 297
Schock, H.W., see Braunger, D. 40 (1996) 97
Schuurmans, F.M., see Leguijt, C. 40 (1996) 297
Sene, C., see Nguyen Cong, H. 40 (1996) 261
Shi, Z., see Zheng, G.F. 40 (1996) 231

Siklos, S.T.C., see Archer, M.D. 40 (1996) 133
Singh, J., see Štulík, P. 40 (1996) 239
Sinke, W.C., see Leguijt, C. 40 (1996) 297
Sproul, A.B., see Zheng, G.F. 40 (1996) 231
Stocks, M.J., A.J. Carr and A.W. Blakers, Texturing of polycrystalline silicon 40 (1996) 33
Štulík, P. and J. Singh, Study of the effect of introducing a bottom ITO layer in an a-Si:H p-i-n type solar cell 40 (1996) 239

Taouk, M., see Ebong, A.U. 40 (1996) 183
Thiry, P.A., see Diatezua, D.M. 40 (1996) 253
Torrance, A.A., see Yang, Y. 40 (1996) 103

Varol, H.S. and A. Hinsch, SnO_2:Sb dip coated films on anodized aluminum selective absorber plates 40 (1996) 273
Verhoef, L.A., see Leguijt, C. 40 (1996) 297

Walter, T., see Braunger, D. 40 (1996) 97
Weeber, A.W., see Leguijt, C. 40 (1996) 297
Wenham, S.R., see Ebong, A.U. 40 (1996) 183
Wenham, S.R., see Zheng, G.F. 40 (1996) 231
Win, S.Z., see Ma, H.L. 40 (1996) 371
Wolter, J.H., see Ragay, F.W. 40 (1996) 5

Yang, Y., A.A. Torrance and J. Rodriguez, The solar hardening of steels: Experiments and predictions 40 (1996) 103
Yin, Y., see Zhang, Q.-C. 40 (1996) 43

Zainal, Z., M.Z. Hussein and A. Ghazali, Cathodic electrodeposition of SnS thin films from aqueous solution 40 (1996) 347
Zhang, D.H., see Ma, H.L. 40 (1996) 371
Zhang, Q.-C., Y. Yin and D.R. Mills, High efficiency Mo–Al_2O_3 cermet selective surfaces for high-temperature application 40 (1996) 43
Zhang, W., see Zheng, G.F. 40 (1996) 231
Zhao, J., see Zheng, G.F. 40 (1996) 89
Zheng, G.F., J. Zhao, M. Gross and E. Chen, Very low light-reflection from the surface of incidence of a silicon solar cell 40 (1996) 89
Zheng, G.F., W. Zhang, Z. Shi, M. Gross, A.B. Sproul, S.R. Wenham and M.A. Green, 16.4% efficient, thin active layer silicon solar cell grown by liquid phase epitaxy 40 (1996) 231

ELSEVIER Solar Energy Materials and Solar Cells 40 (1996) 385–389

Solar Energy Materials and Solar Cells

Subject index to volume 40

Aluminium

SnO_2:Sb dip coated films on anodized aluminum selective absorber plates, H.S. Varol and A. Hinsch 40 (1996) 273

Antireflection coatings

Very low light-reflection from the surface of incidence of a silicon solar cell, G.F. Zheng, J. Zhao, M. Gross and E. Chen 40 (1996) 89

Cadmium selenide, CdSe

Efficient photocatalysts for the reduction of aqueous carbonate and Cr(VI), M.A. Malati, L. Attubato and K. Beaney 40 (1996) 1

Cadmium sulfide, CdS

An 11.4% efficient polycrystalline thin film solar cell based on $CuInS_2$ with a Cd-free buffer layer, D. Braunger, D. Hariskos, T. Walter and H.W. Schock 40 (1996) 97

Poly(3-methylthiophene) structural change effect on characteristics of CdS(Al):PMeT photovoltaic junction, H. Nguyen Cong, C. Sene and P. Chartier 40 (1996) 261

Cadmium telluride, CdTe

Electrical properties of UV photochemically treated CdTe, A.M. Al-Dhafiri 40 (1996) 221

Coating techniques

Spectrally selective silicon paint coatings: Influence of pigment volume concentration ratio on their optical properties, Z.C. Orel, N. Leskovšek, B. Orel and M.G. Hutchins 40 (1996) 197

16.4% efficient, thin active layer silicon solar cell grown by liquid phase epitaxy, G.F. Zheng, W. Zhang, Z. Shi, M. Gross, A.B. Sproul, S.R. Wenham and M.A. Green 40 (1996) 231

Cu

An 11.4% efficient polycrystalline thin film solar cell based on $CuInS_2$ with a Cd-free buffer layer, D. Braunger, D. Hariskos, T. Walter and H.W. Schock 40 (1996) 97

Elsevier Science B.V.

Electrical properties

Electrical properties of UV photochemically treated CdTe, A.M. Al-Dhafiri 40 (1996) 221

Emissivity

High efficiency Mo–Al_2O_3 cermet selective surfaces for high-temperature application, Q.-C. Zhang, Y. Yin and D.R. Mills 40 (1996) 43

Gallium compounds

TPV cell *IV* curve testing with varying black body emission temperatures, intensities, and cell temperatures, J.J. Lin and D.R. Burger 40 (1996) 177

Heat transfer

Heat transfer characteristics in low-temperature latent heat storage systems using salt-hydrates at heat recovery stage, J.C. Choi, S.D. Kim and G.Y. Han 40 (1996) 71

Indium compounds

16.4% efficient, thin active layer silicon solar cell grown by liquid phase epitaxy, G.F. Zheng, W. Zhang, Z. Shi, M. Gross, A.B. Sproul, S.R. Wenham and M.A. Green 40 (1996) 231

Light trapping (concentration)

Texturing of polycrystalline silicon, M.J. Stocks, A.J. Carr and A.W. Blakers 40 (1996) 33

Molybdenum sulfide, MoS_2

Efficient photocatalysts for the reduction of aqueous carbonate and Cr(VI), M.A. Malati, L. Attubato and K. Beaney 40 (1996) 1

Open-circuit voltage

Experimental analysis of the efficiency of heterostructure GaAs–AlGaAs solar cells, F.W. Ragay, A. Martí, G.L. Araújo and J.H. Wolter 40 (1996) 5

Optical properties

Study of the effect of introducing a bottom ITO layer in an a-Si:H p-i-n type solar cell, P. Štulík and J. Singh 40 (1996) 239

Silicon oxynitride multilayers as spectrally selective material for passive radiative cooling applications, D.M. Diatezua, P.A. Thiry, A. Dereux and R. Caudano 40 (1996) 253

p–n heterojunctions

Experimental analysis of the efficiency of heterostructure GaAs–AlGaAs solar cells, F.W. Ragay, A. Martí, G.L. Araújo and J.H. Wolter 40 (1996) 5

A review of analytic solutions for a model *p-n* junction cell under low-injection conditions, M.D. Archer, J.R. Bolton and S.T.C. Siklos 40 (1996) 133

p–n homojunctions

A review of analytic solutions for a model *p-n* junction cell under low-injection conditions, M.D. Archer, J.R. Bolton and S.T.C. Siklos 40 (1996) 133

Photochemistry

Efficient photocatalysts for the reduction of aqueous carbonate and Cr(VI), M.A. Malati, L. Attubato and K. Beaney 40 (1996) 1

Photoelectrodes, TiO_2 and titanates

Efficient photocatalysts for the reduction of aqueous carbonate and Cr(VI), M.A. Malati, L. Attubato and K. Beaney 40 (1996) 1

Photovoltaic effects

Experimental analysis of the efficiency of heterostructure GaAs–AlGaAs solar cells, F.W. Ragay, A. Martí, G.L. Araújo and J.H. Wolter 40 (1996) 5

Photovoltaics, general properties and types

Experimental analysis of the efficiency of heterostructure GaAs–AlGaAs solar cells, F.W. Ragay, A. Martí, G.L. Araújo and J.H. Wolter 40 (1996) 5
A minimum achievable PV electrical generating cost, E.S. Sabisky 40 (1996) 55
The use of oxynitrides for the fabrication of buried contact silicon solar cells, A.U. Ebong, M. Taouk, C.B. Honsberg and S.R. Wenham 40 (1996) 183
Poly(3-methylthiophene) structural change effect on characteristics of CdS(Al):PMeT photovoltaic junction, H. Nguyen Cong, C. Sene and P. Chartier 40 (1996) 261

Polymers

Initial experiments on dew collection in Sweden and Tanzania, T. Nilsson 40 (1996) 23

Salt hydrates

Heat transfer characteristics in low-temperature latent heat storage systems using salt-hydrates at heat recovery stage, J.C. Choi, S.D. Kim and G.Y. Han 40 (1996) 71

Selective surfaces, theory and general materials

High efficiency Mo–Al_2O_3 cermet selective surfaces for high-temperature application, Q.-C. Zhang, Y. Yin and D.R. Mills 40 (1996) 43

Silicon

Very low light-reflection from the surface of incidence of a silicon solar cell, G.F. Zheng, J. Zhao, M. Gross and E. Chen 40 (1996) 89

The use of oxynitrides for the fabrication of buried contact silicon solar cells, A.U. Ebong, M. Taouk, C.B. Honsberg and S.R. Wenham 40 (1996) 183
16.4% efficient, thin active layer silicon solar cell grown by liquid phase epitaxy, G.F. Zheng, W. Zhang, Z. Shi, M. Gross, A.B. Sproul, S.R. Wenham and M.A. Green 40 (1996) 231
Silicon oxynitride multilayers as spectrally selective material for passive radiative cooling applications, D.M. Diatezua, P.A. Thiry, A. Dereux and R. Caudano 40 (1996) 253

Silicon nitride, SiN

The use of oxynitrides for the fabrication of buried contact silicon solar cells, A.U. Ebong, M. Taouk, C.B. Honsberg and S.R. Wenham 40 (1996) 183

Sodium acetate trihydrate

Heat transfer characteristics in low-temperature latent heat storage systems using salt-hydrates at heat recovery stage, J.C. Choi, S.D. Kim and G.Y. Han 40 (1996) 71

Solar absorber–convertors

High efficiency Mo–Al_2O_3 cermet selective surfaces for high-temperature application, Q.-C. Zhang, Y. Yin and D.R. Mills 40 (1996) 43

Solar cells

A minimum achievable PV electrical generating cost, E.S. Sabisky 40 (1996) 55
Very low light-reflection from the surface of incidence of a silicon solar cell, G.F. Zheng, J. Zhao, M. Gross and E. Chen 40 (1996) 89
An 11.4% efficient polycrystalline thin film solar cell based on $CuInS_2$ with a Cd-free buffer layer, D. Braunger, D. Hariskos, T. Walter and H.W. Schock 40 (1996) 97
The use of oxynitrides for the fabrication of buried contact silicon solar cells, A.U. Ebong, M. Taouk, C.B. Honsberg and S.R. Wenham 40 (1996) 183
16.4% efficient, thin active layer silicon solar cell grown by liquid phase epitaxy, G.F. Zheng, W. Zhang, Z. Shi, M. Gross, A.B. Sproul, S.R. Wenham and M.A. Green 40 (1996) 231
Study of the effect of introducing a bottom ITO layer in an a-Si:H p-i-n type solar cell, P. Štulík and J. Singh 40 (1996) 239
Poly(3-methylthiophene) structural change effect on characteristics of CdS(Al):PMeT photovoltaic junction, H. Nguyen Cong, C. Sene and P. Chartier 40 (1996) 261

Solar collectors

SnO_2:Sb dip coated films on anodized aluminum selective absorber plates, H.S. Varol and A. Hinsch 40 (1996) 273

Solar furnace

The solar hardening of steels: Experiments and predictions, Y. Yang, A.A. Torrance and J. Rodriguez 40 (1996) 103

Spectral response

TPV cell *IV* curve testing with varying black body emission temperatures, intensities, and cell temperatures, J.J. Lin and D.R. Burger 40 (1996) 177

Spectrally selective silicon paint coatings: Influence of pigment volume concentration ratio on their optical properties, Z.C. Orel, N. Leskovšek, B. Orel and M.G. Hutchins 40 (1996) 197

Textured surfaces

Texturing of polycrystalline silicon, M.J. Stocks, A.J. Carr and A.W. Blakers 40 (1996) 33

Thermoelectrics

TPV cell *IV* curve testing with varying black body emission temperatures, intensities, and cell temperatures, J.J. Lin and D.R. Burger 40 (1996) 177

Thin film solar cells

Very low light-reflection from the surface of incidence of a silicon solar cell, G.F. Zheng, J. Zhao, M. Gross and E. Chen 40 (1996) 89

Thin films

An 11.4% efficient polycrystalline thin film solar cell based on $CuInS_2$ with a Cd-free buffer layer, D. Braunger, D. Hariskos, T. Walter and H.W. Schock 40 (1996) 97
Solution growth, characterization and applications of zinc sulphide thin films, I.C. Ndukwe 40 (1996) 123
Structural and electrochemical properties of CeO_2 and mixed CeO_2/SnO_2 coatings, Z. Crnjak Orel and B. Orel 40 (1996) 205
16.4% efficient, thin active layer silicon solar cell grown by liquid phase epitaxy, G.F. Zheng, W. Zhang, Z. Shi, M. Gross, A.B. Sproul, S.R. Wenham and M.A. Green 40 (1996) 231
Poly(3-methylthiophene) structural change effect on characteristics of CdS(Al):PMeT photovoltaic junction, H. Nguyen Cong, C. Sene and P. Chartier 40 (1996) 261

Zinc sulfide, ZnS

Solution growth, characterization and applications of zinc sulphide thin films, I.C. Ndukwe 40 (1996) 123